

SYSTEM SENSORS

SYSTEM SENSOR D4120 LOW FLOW SMOKE DETECTOR

D4120



- Outside mounting tabs.
- Patented telescoping sampling tube.
- Built-in reset button.
- Interconnectability for multi-fan shutdown (up to fifty air handlers).
- Patented cover tamper trouble signal.
- Easy to clean.
- 24 VAC/DC or 120/VAC operation.
- High-Low voltage barrier.
- UL 268A listed.
- 1 year warranty

Catalog#	Model#	Description	List\$
W-12660	D4120	Smoke Detector	\$214.00
W-12661	DST 1.5	1.5 Foot Sampling Tube	\$12.00
W-12662	DST 3	3 Foot Sampling Tube	\$16.00
W-12663	DST 5	5 Foot Sampling Tube	\$20.00
W-12664	DST-10	10 Foot Sampling Tube	\$43.00

SAMPLING TUBE FOR ABOVE DETECTOR



SYSTEM SENSOR 2151 LOW VELOCITY PHOTOELECTRIC (NO FLOW/LOW FLOW) DUCT DETECTOR

2151



- Low profile smoke detector design.
- Low standby current.
- Two LED's "blink" in stand by.
- Detector head plugs easily into base.
- Built-in test switch.
- Built-in tamper-resistant feature.
- Air velocity rating 0 to 3000 FPM.
- 120VAC base with built-in shorting spring.
- Designed for mounting on standard electrical box.
- SEM screws for easy wiring and positive wire retention.
- Removable cover and insect screen for field cleaning.
- UL 268A listed.

Catalog#	List\$
W-10564	\$72.00

SMOKE DETECTOR BASE UNIT

B114LP

- 120 VAC base unit for use with 2151 above.

B114LPBT

- 24 VAC/DC base unit for use with 2151 above.



Model#	Catalog#	List\$
B114LP	W-10565	\$83.00
B114LPBT	W-12652	\$75.00

SYSTEM SENSOR CARBON MONOXIDE DETECTOR

- UL 2075
- 12/24 VDC
- Wall or ceiling mounted.
- Code required trouble relay.
- Electro Chemical sensing.



CO1224

Catalog#	List\$
W-12478	\$153.00

Accessory Reference



Required to be used with 2151 detector for in-duct installations. Also works with D4120.

RTS451 Remote Test Station

Catalog#	List\$
W-12476	\$61.00